

(12) United States Patent Halverson et al.

(10) **Patent No.:**

US 9,314,346 B2

(45) Date of Patent:

Apr. 19, 2016

(54) SPINAL IMPLANT

Inventors: **Peter Halverson**, Alpine, UT (US);

Larry L. Howell, Orem, UT (US); Spencer P. Magleby, Provo, UT (US); Anton E. Bowden, Lindon, UT (US)

Assignee: Brigham Young University, Provo, UT

(US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 500 days.

Appl. No.: 12/726,816

(22)Filed: Mar. 18, 2010

(65)**Prior Publication Data**

US 2010/0241232 A1 Sep. 23, 2010

Related U.S. Application Data

- Continuation-in-part of application No. 12/029,046, filed on Feb. 11, 2008, now Pat. No. 8,308,801.
- Provisional application No. 61/210,572, filed on Mar. 19, 2009, provisional application No. 60/901,217, filed on Feb. 12, 2007.
- (51) Int. Cl.

A61F 2/44 (2006.01)A61B 17/70 (2006.01)A61F 2/30 (2006.01)

(52) U.S. Cl.

CPC A61F 2/4425 (2013.01); A61B 17/70 (2013.01); A61F 2002/30014 (2013.01); A61F 2002/30016 (2013.01); A61F 2002/30232 (2013.01);

(Continued)

Field of Classification Search

CPC . A61F 2/4425; A61F 2002/443; A61F 2/442; A61F 2/44 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

3/1976 Hillberry et al. 3.945.053 A 4,267,608 A 5/1981 Bora, Jr. (Continued)

FOREIGN PATENT DOCUMENTS

1020050080493 KR 8/2005 KR 1020060113318 11/2006 (Continued)

OTHER PUBLICATIONS

Jeanneau et al.; "A Compliant Rolling Contact Joint and it's Application in a 3-DOF Planar Parallel Mechanism with Kinematic Analysis"; Proceedings of DETC'04, ASME 2004 Design Engineering Technical Conferences and Computers and Information in Engineering Conference; Sep. 28-Oct. 2, 2004; Salt Lake City, Utah USA. DETC2004-57264, 2004by ASME.

(Continued)

Primary Examiner — Christian Sevilla Assistant Examiner — Si Ming Ku

(74) Attorney, Agent, or Firm — Adam D. Stevens; Kirton **McConkie**

(57)ABSTRACT

A spinal implant includes a first rolling-contact core operably coupled to a first vertebra, said first rolling-contact core having a first convex surface having a first axis, said first convex surface configured to provide a first rolling motion in a first direction to said first vertebra relative to a second vertebra. At least one flexure is connected to said first rolling-contact core, said flexure configured to constrain said first rolling motion.

31 Claims, 13 Drawing Sheets

